



MODEL NUMBER	NOMINAL SIZE (INCHES) W X H X D	ACTUAL SIZE (INCHES) W X H X D	RATED AIR FLOW (CFM)	INITIAL RESISTANCE (IN. W.G.)	MEDIA AREA (SQUARE FEET)
PAF11-STD1	10 X 20 X 1	9-1/2 X 19-1/2 X 3/4	425	0.29	2.6
PAF11-STD1	12 X 20 X 1	11-1/2 X 19-1/2 X 3/4	500	0.29	3.1
PAF11-STD1	12 X 24 X 1	11-3/8 X 23-3/8 X 3/4	600	0.29	3.7
PAF11-STD1	14 X 20 X 1	13-1/2 X 19-1/2 X 3/4	590	0.29	3.8
PAF11-STD1	14 X 25 X 1	13-1/2 X 24-1/2 X 3/4	730	0.29	4.8
PAF11-STD1	15 X 20 X 1	14-1/2 X 19-1/2 X 3/4	630	0.29	4.0
PAF11-STD1	16 X 20 X 1	15-1/2 X 24-1/2 X 3/4	670	0.29	4.3
PAF11-STD1	16 X 25 X 1	15-1/2 X 24-1/2 X 3/4	840	0.29	5.4
PAF11-STD1	18 X 24 X 1	17-3/8 X 23-3/8 X 3/4	900	0.29	5.7
PAF11-STD1	20 X 20 X 1	19-1/2 X 19-1/2 X 3/4	840	0.29	5.5
PAF11-STD1	20 X 25 X 1	19-1/2 X 24-1/2 X 3/4	1050	0.29	6.9
PAF11-STD1	24 X 24 X 1	23-3/8 X 23-3/8 X 3/4	1200	0.29	7.7
PAF11-STD1	25 X 25 X 1	24-1/2 X 24-1/2 X 3/4	1310	0.28	8.7

STANDARD CONSTRUCTION

1. White Synthetic Media
2. 14 Pleats Per Foot
3. Expanded Metal Pleat Supports
4. Moisture Resistant Beverage Board Frame
5. Double Wall Frame

NOTES

1. MERV 11 per ASHRAE Standard 52.2-2012
Tested at 295 FPM Face Velocity on 24x24x1
2. Final Resistance: 1.0" W.G.
3. Rated Velocity: 300 FPM
4. Classified per UL Standard 900 for Flammability
5. Maximum Operating Temperature: 200 deg. F



100 River Ridge Circle
Jeffersonville, IN 47130
P: 866-925-2247
F: 866-601-1809
www.purolatorair.com

CONTACT FACTORY TO
VERIFY REVISION LEVEL

TOLERANCES UNLESS OTHERWISE SPECIFIED

FRACTIONAL -
DECIMAL -
ANGLES -

ALL DIMENSIONS IN INCHES

DRAWING NAME

PAF 11 (1" DEPTH)

APPROVED BY

K. Quinn

SPECIFICATION NO.

MKT-P-00574

PAGE

1 OF 1

SCALE

NONE

DWG. SIZE

A

REVISION

A

REVISION DATE

08-07-14

CONFIDENTIAL - DO NOT COPY. THIS MATERIAL IS TRADE SECRET AND PROPRIETARY BEING EXCLUSIVELY OWNED BY CLC AIR. THE EXPRESSION OF THE INFORMATION CONTAINED HEREIN IS PROTECTED UNDER FEDERAL COPYRIGHT LAWS AND ALL COPYING IS PROHIBITED AND MAY BE SUBJECT TO CRIMINAL PENALTIES.