



Model Number	Nominal Size (Inches) W x H x D	Actual Size (Inches) W x H x D	Rated Air Flow (CFM)	Initial Resistance (IN W.G.)	Media Area (Square Feet)
SL95-4412	24 x 24 x 12	23-3/8 x 23-3/8 x 11-1/2	2000	.65	124
SL95-0512	20 x 25 x 12	19-3/8 x 24-3/8 x 11-1/2	1750	.65	106
SL95-0412	20 x 24 x 12	19-3/8 x 23-3/8 x 11-1/2	1650	.65	102
SL95-0012	20 x 20 x 12	19-3/8 x 19-3/8 x 11-1/2	1400	.65	83
SL95-6512	16 x 25 x 12	15-3/8 x 24-3/8 x 11-1/2	1400	.65	81
SL95-6012	16 x 20 x 12	15-3/8 x 19-3/8 x 11-1/2	1100	.65	63
SL95-2412	12 x 24 x 12	11-3/8 x 23-3/8 x 11-1/2	1000	.65	56
SL85-4412	24 x 24 x 12	23-3/8 x 23-3/8 x 11-1/2	2000	.60	124
SL85-0512	20 x 25 x 12	19-3/8 x 24-3/8 x 11-1/2	1750	.60	106
SL85-0412	20 x 24 x 12	19-3/8 x 23-3/8 x 11-1/2	1650	.60	102
SL85-0012	20 x 20 x 12	19-3/8 x 19-3/8 x 11-1/2	1400	.60	83
SL85-6512	16 x 25 x 12	15-3/8 x 24-3/8 x 11-1/2	1400	.60	81
SL85-6012	16 x 20 x 12	15-3/8 x 19-3/8 x 11-1/2	1100	.60	63
SL85-2412	12 x 24 x 12	11-3/8 x 23-3/8 x 11-1/2	1000	.60	56
SL65-4412	24 x 24 x 12	23-3/8 x 23-3/8 x 11-1/2	2000	.43	124
SL65-0512	20 x 25 x 12	19-3/8 x 24-3/8 x 11-1/2	1750	.43	106
SL65-0412	20 x 24 x 12	19-3/8 x 23-3/8 x 11-1/2	1650	.43	102
SL65-0012	20 x 20 x 12	19-3/8 x 19-3/8 x 11-1/2	1400	.43	83
SL65-6512	16 x 25 x 12	15-3/8 x 24-3/8 x 11-1/2	1400	.43	81
SL65-6012	16 x 20 x 12	15-3/8 x 19-3/8 x 11-1/2	1100	.43	63
SL65-2412	12 x 24 x 12	11-3/8 x 23-3/8 x 11-1/2	1000	.43	56

STANDARD CONSTRUCTION

1. High Efficiency, Microglass Paper Media
2. Corrugated Aluminum Separators With Rolled Edges
3. High Loft Microglass Wrap Around Media Pack
4. 24 Gauge Galvanized Steel Cell Sides
5. Header on Air Entering Side: Single Piece U-Channel
6. Expanded Metal Grid on Air Leaving Side

NOTES

1. Average Efficiency, MERV (492 FPM on 24x24 Face Size)
90-95% ASHRAE 52.1-1992, MERV 14 ASHRAE 52.2-2007
80-85% ASHRAE 52.1-1992, MERV 13 ASHRAE 52.2-2007
60-65% ASHRAE 52.1-1992, MERV 11 ASHRAE 52.2-2007
2. Final Resistance: 1.5" W.G.
3. Rated Velocity 12" Deep - 500 FPM
4. Class 1 Filter Per U.L. Standard 900
5. Maximum Operating Temperature: 350 deg. F
6. Optional Gasket Available
U - Upstream Gasket (Ex: SL95F-4412-U)
D - Downstream Gasket
UD- Both Sides
7. Optional 1-1/8" Header ("C" Header) Available
(Ex: SL95C-4412)
8. Special Sizes Available

Purolator
P.O. Box 32578
Louisville, KY 40232
P: 866-925-2247
F: 502-961-0930
www.purolatorair.com

**CONTACT FACTORY TO
VERIFY REVISION LEVEL**

**TOLERANCES
UNLESS OTHERWISE SPECIFIED**

- FRACTIONAL -
- DECIMAL -
- ANGLES -

ALL DIMENSIONS IN INCHES

DRAWING NAME SERVA-CELL SINGLE HEADER - 12"			
APPROVED BY <i>K. Quinn</i>	SPECIFICATION NO. MKT-P-00134	PAGE 1 OF 1	
SCALE NONE	DWG. SIZE A	REVISION C	REVISION DATE 06-15-09

CONFIDENTIAL - DO NOT COPY. THIS MATERIAL IS TRADE SECRET AND PROPRIETARY BEING EXCLUSIVELY OWNED BY CLC AIR. THE EXPRESSION OF THE INFORMATION CONTAINED HEREIN IS PROTECTED UNDER FEDERAL COPYRIGHT LAWS AND ALL COPYING IS PROHIBITED AND MAY BE SUBJECT TO CRIMINAL PENALTIES.