



Model Number	Nominal Size (Inches) W x H x D	Actual Size (Inches) W x H x D	Rated Air Flow (CFM)	Initial Resistance (IN W.G.)	Media Area (Square Feet)
SL95-4406	24 x 24 x 6	23-3/8 x 23-3/8 x 5-7/8	1000	.38	56
SL95-0506	20 x 25 x 6	19-3/8 x 24-3/8 x 5-7/8	875	.38	48
SL95-0406	20 x 24 x 6	19-3/8 x 23-3/8 x 5-7/8	825	.38	46
SL95-0006	20 x 20 x 6	19-3/8 x 19-3/8 x 5-7/8	700	.38	37
SL95-6506	16 x 25 x 6	15-3/8 x 24-3/8 x 5-7/8	700	.38	37
SL95-6006	16 x 20 x 6	15-3/8 x 19-3/8 x 5-7/8	550	.38	28
SL95-2406	12 x 24 x 6	11-3/8 x 23-3/8 x 5-7/8	550	.38	25
SL85-4406	24 x 24 x 6	23-3/8 x 23-3/8 x 5-7/8	1000	.38	56
SL85-0506	20 x 25 x 6	19-3/8 x 24-3/8 x 5-7/8	875	.38	48
SL85-0406	20 x 24 x 6	19-3/8 x 23-3/8 x 5-7/8	825	.38	46
SL85-0006	20 x 20 x 6	19-3/8 x 19-3/8 x 5-7/8	700	.38	37
SL85-6506	16 x 25 x 6	15-3/8 x 24-3/8 x 5-7/8	700	.38	37
SL85-6006	16 x 20 x 6	15-3/8 x 19-3/8 x 5-7/8	550	.38	28
SL85-2406	12 x 24 x 6	11-3/8 x 23-3/8 x 5-7/8	550	.38	25
SL65-4406	24 x 24 x 6	23-3/8 x 23-3/8 x 5-7/8	1000	.23	56
SL65-0506	20 x 25 x 6	19-3/8 x 24-3/8 x 5-7/8	875	.23	48
SL65-0406	20 x 24 x 6	19-3/8 x 23-3/8 x 5-7/8	825	.23	46
SL65-0006	20 x 20 x 6	19-3/8 x 19-3/8 x 5-7/8	700	.23	37
SL65-6506	16 x 25 x 6	15-3/8 x 24-3/8 x 5-7/8	700	.23	37
SL65-6006	16 x 20 x 6	15-3/8 x 19-3/8 x 5-7/8	550	.23	28
SL65-2406	12 x 24 x 6	11-3/8 x 23-3/8 x 5-7/8	550	.23	25

STANDARD CONSTRUCTION

1. High Efficiency, Microglass Paper Media
2. Corrugated Aluminum Separators With Rolled Edges
3. High Loft Microglass Wrap Around Media Pack
4. 24 Gauge Galvanized Steel Cell Sides
5. Header on Air Entering Side: Single Piece U-Channel
6. Expanded Metal Grid on Air Leaving Side

NOTES

1. Average Efficiency, MERV
 - 90-95% ASHRAE 52.1-1992, MERV 14 ASHRAE 52.2-1999
 - 80-85% ASHRAE 52.1-1992, MERV 13 ASHRAE 52.2-1999
 - 60-65% ASHRAE 52.1-1992, MERV 11 ASHRAE 52.2-1999
2. Final Resistance: 1.5" W.G.
3. Rated Velocity 6" Deep - 250 FPM
4. Class 1 Filter Per U.L. Standard 900
5. Maximum Operating Temperature: 350 deg. F
6. Optional Gasket Available (Rated Temperature 180 deg. F)
 - U - Upstream Gasket (Ex: SL95F-4406-U)
 - D - Downstream Gasket
 - UD - Both Sides
7. Optional 1-1/8" Header ("C" Header) Available (Ex: SL95C-4406)
8. Special Sizes Available



P.O. Box 32578
 Louisville, KY 40232
 P: 866-925-2247
 F: 502-961-0930

**CONTACT FACTORY TO
 VERIFY REVISION LEVEL**

**TOLERANCES
 UNLESS OTHERWISE SPECIFIED**

FRACTIONAL -
 DECIMAL -
 ANGLES -

ALL DIMENSIONS IN INCHES

DRAWING NAME

SERVA-CELL SINGLE HEADER - 6"

APPROVED BY

K. Clum

SPECIFICATION NO.

MKT-P-00536

PAGE
1 OF 1

SCALE

NONE

DWG. SIZE

A

REVISION

NEW

REVISION DATE

05-04-07

CONFIDENTIAL - DO NOT COPY. THIS MATERIAL IS TRADE SECRET AND PROPRIETARY BEING EXCLUSIVELY OWNED BY CLC AIR. THE EXPRESSION OF THE INFORMATION CONTAINED HEREIN IS PROTECTED UNDER FEDERAL COPYRIGHT LAWS AND ALL COPYING IS PROHIBITED AND MAY BE SUBJECT TO CRIMINAL PENALTIES.