



MODEL	NOMINAL SIZE (INCHES)	ACTUAL SIZE (INCHES)	RATED AIR FLOW (CFM)	INITIAL RESISTANCE (IN. W.G.)	MERV / MERV-A	MEDIA AREA (SQUARE FEET)
SLB95-4406	24 X 24 X 6	23-3/8 X 23-3/8 X 5-7/8	1000	0.38	14 / 14-A	64
SLB95-0506	20 X 25 X 6	19-3/8 X 24-3/8 X 5-7/8	875	0.38	14 / 14-A	56
SLB95-0406	20 X 24 X 6	19-3/8 X 23-3/8 X 5-7/8	825	0.38	14 / 14-A	54
SLB95-0006	20 X 20 X 6	19-3/8 X 19-3/8 X 5-7/8	700	0.38	14 / 14-A	45
SLB95-6506	16 X 25 X 6	15-3/8 X 24-3/8 X 5-7/8	700	0.38	14 / 14-A	44
SLB95-6006	16 X 20 X 6	15-3/8 X 19-3/8 X 5-7/8	550	0.38	14 / 14-A	35
SLB95-2406	12 X 24 X 6	11-3/8 X 23-3/8 X 5-7/8	500	0.38	14 / 14-A	31
SLB85-4406	24 X 24 X 6	23-3/8 X 23-3/8 X 5-7/8	1000	0.35	13 / 13-A	64
SLB85-0506	20 X 25 X 6	19-3/8 X 24-3/8 X 5-7/8	875	0.35	13 / 13-A	56
SLB85-0406	20 X 24 X 6	19-3/8 X 23-3/8 X 5-7/8	825	0.35	13 / 13-A	54
SLB85-0006	20 X 20 X 6	19-3/8 X 19-3/8 X 5-7/8	700	0.35	13 / 13-A	45
SLB85-6506	16 X 25 X 6	15-3/8 X 24-3/8 X 5-7/8	700	0.35	13 / 13-A	44
SLB85-6006	16 X 20 X 6	15-3/8 X 19-3/8 X 5-7/8	550	0.35	13 / 13-A	35
SLB85-2406	12 X 24 X 6	11-3/8 X 23-3/8 X 5-7/8	500	0.35	13 / 13-A	31
SLB65-4406	24 X 24 X 6	23-3/8 X 23-3/8 X 5-7/8	1000	0.20	11 / 11-A	64
SLB65-0506	20 X 25 X 6	19-3/8 X 24-3/8 X 5-7/8	875	0.20	11 / 11-A	56
SLB65-0406	20 X 24 X 6	19-3/8 X 23-3/8 X 5-7/8	825	0.20	11 / 11-A	54
SLB65-0006	20 X 20 X 6	19-3/8 X 19-3/8 X 5-7/8	700	0.20	11 / 11-A	45
SLB65-6506	16 X 25 X 6	15-3/8 X 24-3/8 X 5-7/8	700	0.20	11 / 11-A	44
SLB65-6006	16 X 20 X 6	15-3/8 X 19-3/8 X 5-7/8	550	0.20	11 / 11-A	35
SLB65-2406	12 X 24 X 6	11-3/8 X 23-3/8 X 5-7/8	500	0.20	11 / 11-A	31

**STANDARD CONSTRUCTION**

1. High Efficiency, Microglass Paper Media
2. Corrugated Aluminum Separators With Rolled Edges
3. High Loft Microglass Wrap Around Media Pack
4. 24 Gauge Galvanized Steel Cell Sides
5. Expanded Metal Grid on Air Leaving Side
6. (4) Retainer Holes for Spring Latches

**NOTES**

1. MERV per ASHRAE 52.2-2007, Appendix J  
Tested at 492 FPM on 24x24x12 Standard Size
2. Final Resistance: 1.5" W.G.
3. Rated Velocity - 250 FPM
4. Classified per U.L. Standard 900 for Flammability Only
5. Maximum Operating Temperature: 350 deg. F
6. Optional Gasket Available - 1/4 x 3/4 Dovetail Neoprene (180 deg F)  
U - Upstream Gasket (Ex: SLB95F 24X24X12 U)  
D - Downstream Gasket  
UD - Both Sides
7. Optional Gasket Available - 1/4 x 1/2 Foam (180 deg F)  
SA - Side Access  
P - Perimeter
8. Special Sizes Available



100 River Ridge Circle  
Jeffersonville, IN 47130  
P: 866-925-2247  
F: 502-961-0930  
www.purolatorair.com

**CONTACT FACTORY TO  
VERIFY REVISION LEVEL**

**TOLERANCES  
UNLESS OTHERWISE SPECIFIED**

FRACTIONAL -  
DECIMAL -  
ANGLES -

ALL DIMENSIONS IN INCHES

DRAWING NAME

**SERVA-CELL FULL BOX - 6" DEPTH**

APPROVED BY

*K. Oum*

SPECIFICATION NO.

MKT-00617

PAGE

1 OF 1

SCALE

NONE

DWG. SIZE

A

REVISION

NEW

REVISION DATE

06-06-12

CONFIDENTIAL - DO NOT COPY. THIS MATERIAL IS TRADE SECRET AND PROPRIETARY BEING EXCLUSIVELY OWNED BY CLC AIR. THE EXPRESSION OF THE INFORMATION CONTAINED HEREIN IS PROTECTED UNDER FEDERAL COPYRIGHT LAWS AND ALL COPYING IS PROHIBITED AND MAY BE SUBJECT TO CRIMINAL PENALTIES.